

Model No.: VKPC6AU28GCMxxx-yy

Description: PVC 4PR 28AWG U/UTP CAT6A Patch Cord



Application

Vectorkom category 6A dual jacketed patch cords (U/UTP) allows for data transmission between patch panels, outlets and/or IT equipment installed in data center or terminal users. The metallic tape between dual jacket and these dual jackets providing optimum protection against EMI to pass alien crosstalk, Backwards compatible with Cat5e and Cat6 application.

Characteristics

Type of cable 4 pair cables Non-plenum cable
Conductor Material Copper, 28AWG (7x0.127+/-0.008MM)

Cable insulation HDPE, 0.68+/-0.05MM OD

Cable jacket PVC, 5.3+/-0.2MM OD for outter jacket, 4.0+/-0.15MM for inner jacket

Assembly style Plug to Plug, with molded PE+EVA snagless boot Plug contact material Phosphor bronze with 50 micron-inches gold plating

Crimping depth 6.02+/-0.13MM Temperature -20 C to +70 C

Performance 100% FLUKE tested component compliant

Certification ACMA compliant - RCM certified

Cable marking VKPC6AU28GCMxxx-yy PVC 4PR 28AWG U/UTP CAT6A TIA-568.2-D (batch no.)

(Note: -yy indicates cable jacke color, WE for white, BL for Black, GR for green, BU for blue, RD for Red, YL for Yellow, OR for orange, GY for grey, and custom color is available.)

Standards

EIA/TIA 568.2-D

ISO/IEC 11801-1 / ISO/IEC 11801-2

EN 50173-1 / EN 50173-2

AS/CA S008:2010+A1/2014

• IEC 61935-2:2010 Ed. 3.0

Ordering Reference

Part Number VKPC6AU28GCMxxx-yy

xxx indicates cable length -yy indicates cable jacket color

005 for 0.5 meters WE for White 010 for 1.0 meters BL for Black 015 for 1.5 meters **GR** for Green 020 for 2.0 meters BU for Blue 030 for 3.0 meters RD for Red 050 for 5.0 meters YL for Yellow 070 for 7.0 meters **OR** for Orange 100 for 10 meters GY for Grey

150 for 15 meters Custom color is available

Custom length is available